Γ . .

] 1/6 j





FIG. 1


Attorney's Docket: 067856.0235
For: Console Information Server System and Method
By: McGraw, et al.





the first first that the state of the

He of the top of the first of the self-


٦








	MANAGEMENT BOARD	SLOT 1	SLOT 2	BACKUP CS	
CASE 1	CPU - PRESENT (CS)	PRESENT	PRESENT	SLOT 1	
CASE 2	CPU - PRESENT (CS)	ABSENT	PRESENT	SLOT 2	
CASE 3	ABSENT	PRESENT (CS)	PRESENT	SLOT 2	
CASE 4	-Ptg - PRESENT	PRESENT (CS)	PRESENT	SLOT 2	
CPU FIG. 6					



. . .



FIELDS	VALUE	FUNCTION	
CMD	0	THIS IMPLIES IT IS A COMMAND MESSAGE	
SCOPE	0 OR 1	0: IT IS A CHASSIS LOCAL MESSAGE	
		1: IT IS AN INTER CHASSIS MESSAGE	
		NOTE: WHEN THE SCOPE IS DEFINED AS LOCAL ONLY THE SLOT ID FIELD IS PRESENTED IN THE <slot-identifier>. ON THE OTHER HAND WHEN THE SCOPE IS DEFINED AS INTER CHASSIS BOTH THE SLOT ID AND CHASSIS ID FIELDS ARE PRESENTED IN THE <slot-identifier></slot-identifier></slot-identifier>	
MULTI-BYTE	0 OR 1	0: NO DATA BYTES FOLLOWING	
		1: DATA BYTES FOLLOWING	
RSVD	UNASSIGNED	•	
RSVD	UNASSIGNED		
TASKS	00H-07H	00: RECEIVE COMMAND ~ 220	
		01: TRANSMIT COMMAND ~ 222	
		02: IDENTIFY COMMAND ~ 224	
5		03: STATUS COMMAND ~ 226	
		04: Re_sync \(\square 228 \)	
		05: SET - 230	
		06: GET - 232	
		07: IDENTIFY CHASSIS COMMAND - 234	

FIG. 9

7	7 6	5 5	5 4		3	2 1	()
	ACK	SCOPE	MULTI-BYTE	EXTENDED	RSVD	ERROR	WATERMARK	DATA
	RSVD	RSVD	RSVD	RSVD	FNC NOT SUPPORTED	NAK	HEALTH	OVERRUN

FIG. 10A

FIG. 10B 36/6

FIELDS	VALUE	FUNCTION	
ACK	1	THIS IMPLIES IT IS AN ACKNOWLEDGE MESSAGE	
SCOPE*	0 OR 1	O: IT IS A CHASSIS LOCAL MESSAGE 1: IT IS AN INTER CHASSIS MESSAGE	
		NOTE: WHEN THE SCOPE IS DEFINED AS LOCAL ONLY THE SLOT ID FIELD IN THE PRESENTED IN THE <slot-identifier>. ON THE OTHER HAND WHEN THE SCOPE IS DEFINED AS INTER CHASSIS BOTH THE SLOT ID AND CHASSIS ID FIELDS ARE PRESENTED IN THE <slot-identifier></slot-identifier></slot-identifier>	
		*SLAVE BLADES NEED NOT SET THIS FIELD. IT IS INTENDED TO BE ADDED BY INTER-CHASSIS COMMUNICATION BOARD ALONG WITH THE CHASSIS ID AND SLOT ID	
MULTI-BYTE	0 OR 1	0: NO DATA BYTES FOLLOWING 1: DATA BYTES FOLLOWING	
EXTEND ACK	0 OR 1	0: IMPLIES ACK FIELD IS ONLY 1 BYTE 1: IMPLIES ACK FIELD IS 2 BYTES	
RSVD	UNASSIGNED	RESERVED FOR FUTURE USE	
ERROR	0 OR 1	0: NO ERROR IN PREVIOUS COMMAND 1: ERROR IN PREVIOUS COMMAND	
WATERMARK	0 OR 1	0: DATA IS LESS THAN 3/4 SIZE OF AVAILABLE BUFFER 1: DATA IS LESS THAN 3/4 SIZE OF AVAILABLE BUFFER	
DATA	*0 OR 1	0: NO DATA AVAILABLE FOR TRANSFER 1: DATA AVAILABLE FOR TRANSFER	

FIG. 10C

FIELDS	VALUE	FUNCTION	
RSVD	UNASSIGNED	RESERVED FOR FUTURE USE	
RSVD	UNASSIGNED	RESERVED FOR FUTURE USE	
RSVD	UNASSIGNED	RESERVED FOR FUTURE USE	
RSVD	UNASSIGNED	RESERVED FOR FUTURE USE	
FNC NOT SUPPORTED	0 OR 1	0: THE FUNCTION REQUESTED WAS O.K. 1: THE FUNCTION REQUESTED IS NOT SUPPORTED ON THE BLADE	
NACK	0 OR 1	0: THE BLADE CAN RESPOND TO MASTER'S REQUEST 1: THE BLADE NOTIFIES THE MASTER TO REQUEST AT A LATER TIME AS THE BLADE IS BUSY	
HEALTH	0 OR 1	0: CPU NOT FUNCTIONAL (SLEEP) 1: CPU FUNCTIONAL	
OVERRUN	0 OR 1	0: DATA IN BUFFER HAS NOT BEEN OVERRUN 1: DATA IN BUFFER HAS BEEN OVERRUN	